Serial No. 10/722,021 Stewart Case No. IS01459MCG

Amendments to the Claims:

1. (Original) A connection controller, comprising:

a network topology cache coupled to receive network topology data of a network; a packing algorithm coupled to receive a requested traffic pattern of a packet, wherein the packing algorithm computes an actual traffic pattern using the network

non-interfering network; and

a logical network state entity coupled to communicate the actual traffic pattern to a source corresponding to the packet.

topology data and the requested traffic pattern such that the network operates as a strictly

- 2. (Currently Amended) The connection controller of claim 1, wherein the connection controller calculates a plurality of routing trees for a plurality of InfiniBand switches in the network, wherein the connection controller calculates a plurality of DLIDs Destination Location Identifiers (DLID) and a set of forwarding instructions for each of the plurality of InfiniBand switches, wherein each of the plurality of DLIDs corresponds to one of the plurality of routing trees and one of a plurality of destinations in the network, and wherein the connection controller populates a forwarding table of each of the plurality of InfiniBand switches with the plurality of DLIDs and the set of forwarding instructions.
- 3. (Currently Amended) The connection controller of claim 1, wherein computing an actual traffic pattern comprises executing a rearrangement algorithm and assigning one of a plurality of Destination Location Identifiers (DLID) to the packet such that the network operates as a strictly non-interfering network.
- 4. (Currently Amended) The connection controller of claim 3, wherein the packet follows a path through at least a portion of a plurality of InfiniBand switches in the network, and wherein each of the portion of the plurality of InfiniBand switches forwards the packet according to the one of the plurality of DLIDs assigned to the packet such that the network operates as a strictly non-interfering network.

Serial No. 10/722,021

Stewart

Case No. IS01459MCG

5. (Currently Amended) The connection controller of claim 4, wherein each of

the portion of the plurality of InfiniBand switches looks up the one of the plurality of

DLIDs assigned to the packet in a forwarding table at each of the portion of the plurality

of InfiniBand switches.

6. (Currently Amended) The connection controller of claim 4, wherein each of

the portion of the plurality of InfiniBand switches forwards the packet in accordance with

the one of the plurality of DLIDs assigned to the packet as found in a forwarding table at

each the portion of the plurality of InfiniBand switches.

7. (Original) The connection controller of claim 1, wherein the network is a Clos

network.

8. (Currently Amended) A connection controller comprising a computer-readable

medium containing computer instructions for instructing a processor to perform a method

of populating a forwarding table, the instructions comprising:

calculating a plurality of routing trees for a plurality of InfiniBand switches in a

network;

calculating a plurality of DLIDs Destination Location Identifiers (DLID) and a set

of forwarding instructions for each of the plurality of InfiniBand switches, wherein each

of the plurality of DLIDs corresponds to one of the plurality of routing trees and one of a

plurality of end nodes and wherein the forwarding instructions create paths appropriate to

make the network operate as a strictly non-interfering network; and

populating the forwarding table of each of the plurality of InfiniBand switches in

the network with the plurality of DLIDs and the set of forwarding instructions.

9. (Original) The connection controller of claim 8, wherein the network is a Clos

network.

4

Serial No. 10/722,021

Stewart

Case No. IS01459MCG

10. (Original) The connection controller of claim 8, wherein each of the plurality of end nodes comprises a destination, and wherein the destination is identified by a BaseLID.

- 11. (Original) The connection controller of claim 8, wherein calculating the plurality of routing trees comprises for each spine node in the network, calculating a shortest path from the spine node to each of the plurality of end nodes.
- 12. (Currently Amended) The connection controller of claim 8, wherein each of the plurality of routing trees comprises at least a portion of the plurality of InfiniBand switches and corresponding plurality of links that form a shortest path from one of the plurality of end nodes to a spine node of the network.
- 13. (Currently Amended) A connection controller comprising a computerreadable medium containing computer instructions for instructing a processor to perform a method of forwarding a packet, wherein the packet is created at a source and is addressed to a destination within a network, the instructions comprising:

executing a rearrangement algorithm for the network;

assigning one of a plurality of DLIDs <u>Destination Location Identifiers (DLID)</u> to the packet; and

the packet following a path through at least a portion of a plurality of InfiniBand switches from the source to the destination, wherein each of the portion of the plurality of InfiniBand switches forward the packet according to the one of the plurality of DLIDs assigned to the packet and wherein the network operates as a strictly non-interfering network.

14. (Canceled)

15. (Original) The connection controller of claim 13, wherein the network is a Clos network.

Serial No. 10/722,021 Stewart Case No. IS01459MCG

16. (Currently Amended) The connection controller of claim 13, wherein the packet following the path comprises looking up the one of the plurality of DLIDs assigned to the packet in a forwarding table at each of the portion of the plurality of InfiniBand switches along the path from the source to the destination.

17. (Currently Amended) The connection controller of claim 13, wherein the packet following the path comprises each of the portion of the plurality of InfiniBand switches forwarding the packet in accordance with the one of the plurality of DLIDs assigned to the packet as found in a forwarding table at each the portion of the plurality of InfiniBand switches.